

Page 1/7

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.01.2020 Version number 1 Revision: 21.10.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: RUCK® Instrumenten Pflegeöl
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

PRISMAN GmbH

Otto Hahn Ring 6-18

D-64653 Lorsch

Germany

· Further information obtainable from:

Abteilung Produktsicherheit

Alexander.Metz@prisman.de

· 1.4 Emergency telephone number: ++49 (0)6251 866980-0, Mo - Fr 8-18 Uhr

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Printing date 07.01.2020 Version number 1 Revision: 21.10.2019

Trade name: RUCK® Instrumenten Pflegeöl

· Additional information:

(Contd. of page 1)

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Keep out of the reach of children

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:				
	propane	25-50%		
EINECS: 200-827-9	🚸 Flam. Gas 1, H220; Press. Gas C, H280			
	butane, pure	10-25%		
EINECS: 203-448-7	♦ Flam. Gas 1, H220; ♦ Acute Tox. 3, H331; Press. Gas C, H280			

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 07.01.2020 Version number 1 Revision: 21.10.2019

Trade name: RUCK® Instrumenten Pflegeöl

See Section 13 for disposal information.

(Contd. of page 2)

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

Not required.

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Rubber gloves

- · For the permanent contact gloves made of the following materials are suitable: Neoprene gloves
- · As protection from splashes gloves made of the following materials are suitable: Butyl rubber, BR

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.01.2020 Version number 1 Revision: 21.10.2019

Trade name: RUCK® Instrumenten Pflegeöl

(Contd. of page 3)

Nitrile rubber, NBR Natural rubber, NR

· Eye protection: Not required.



Tightly sealed goggles

9.1 Information on basic physical and chemical properties					
General Information					
Appearance: Form:	Aerosol				
Colour:	According to product specification				
Odour:	Characteristic				
Odour threshold:	Not determined.				
pH-value:	Not determined.				
Change in condition					
Melting point/freezing point:	Undetermined.				
Initial boiling point and boiling range					
Flash point:	-97 °C				
Flammability (solid, gas):	Not applicable.				
Ignition temperature:	365 °C				
Decomposition temperature:	Not determined.				
Auto-ignition temperature:	Product is not selfigniting.				
Explosive properties:	Product is not explosive. However, formation of explosive a vapour mixtures are possible.				
Explosion limits:					
Lower:	1.5 Vol %				
Upper:	10.9 Vol %				
Vapour pressure at 20 °C:	8300 hPa				
Density at 20 °C:	0.66 g/cm ³				
Relative density	Not determined.				
Vapour density	Not determined.				
Evaporation rate	Not applicable.				
Solubility in / Miscibility with					
water:	Not miscible or difficult to mix.				
Partition coefficient: n-octanol/water:	Not determined.				
Viscosity:					
Dynamic:	Not determined.				
Kinematic:	Not determined.				
Solvent content:					
Organic solvents:	60.0 %				
VOC (EC)	59				

according to 1907/2006/EC, Article 31

Printing date 07.01.2020 Version number 1 Revision: 21.10.2019

Trade name: RUCK® Instrumenten Pflegeöl

(Contd. of page 4)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h 3290 mg/l (rat)

106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Subacute to chronic toxicity: Not determined
- · Toxicokinetics, metabolism and distribution Not determined
- · Acute effects (acute toxicity, irritation and corrosivity) Vapours may cause drowsiness and dizziness.
- · Sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Not determined
- · Germ cell mutagenicity Not determined
- · Carcinogenicity None
- · Reproductive toxicity Not determined
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 07.01.2020 Version number 1 Revision: 21.10.2019

Trade name: RUCK® Instrumenten Pflegeöl

(Contd. of page 5)

- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST	
	gases in pressure containers and discarded chemicals	
16 05 04	gases in pressure containers (including halons) containing dangerous substances	

· Uncleaned packaging:

Marpol and the IBC Code

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	DII	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable	
· 14.3 Transport hazard class(es) · ADR		
· Class · Label	2 5F Gases. 2.1	
· IMDG, IATA		
· Class · Label	2.1 2.1	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Gases. - F-D,S-U	

Not applicable.

according to 1907/2006/EC, Article 31

Printing date 07.01.2020 Version number 1 Revision: 21.10.2019

Trade name: RUCK® Instrumenten Pflegeöl

		(Contd. of page 6)
· Transport/Additional information:		
· ADR		
 Excepted quantities (EQ): 	E0	
Limited quantities (LQ)	1L	
Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
· Transport category	2	
Tunnel restriction code	D	
· IMDG		
· Limited quantities (LQ)	1L	
Excepted quantities (EQ)	Code: E0	
,	Not permitted as Excepted Quantity	
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008 GHS label elements
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H331 Toxic if inhaled.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1 Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure - Compressed gas

Acute Tox. 3: Acute toxicity - inhalation - Category 3

 \cdot * Data compared to the previous version altered.